

THEORY & OBJECTIVE

SURVEYING

*By
Team of
Engineers Academy*

- State Engineering Services Examinations.
- Public Sector Examinations.
- JEn (SSC, DMRC & State Level).
- Other Technical Competitive Exams.



ENGINEERS ACADEMY[®]

Your GATEway to Professional Excellence

IES • GATE • PSUs • JTO • IAS • NET

CORPORATE OFFICE

100-102, Ram Nagar, Bambala Puliya, Tonk Road, Pratap Nagar, Jaipur-302033

Ph.: + 91-8094441777

Website : www.engineersacademy.org | **Email:** info@engineersacademy.org

Ajmer | Jaipur | Kota | Jodhpur | Bhilwara | Delhi | Patna | Lucknow | LPU | Ludhiana | Jalandhar | Kanpur | Allahabad

CONTENTS

S.No.	TOPIC	Page No.
01.	Surveying Principle's	1 – 6
	Objective Practice Sheet	7 – 10
02.	Distance Measuring Instruments	11 – 45
	Objective Practice Sheet	46 – 58
03.	Levelling	59 – 94
	Objective Practice Sheet	95 – 108
04.	Plane Table Surveying	109 – 116
	Objective Practice Sheet	117 – 122
05.	Compass Surveying	123 – 138
	Objective Practice Sheet	139 – 147
06.	Horizontal and Vertical Distance	148 – 169
	Objective Practice Sheet	170 – 185
07.	Astronomy	186 – 206
	Objective Practice Sheet	207 – 213
08.	Photogrammetry	214 – 233
	Objective Practice Sheet	234 – 241
09.	Curves	242 – 261
	Objective Practice Sheet	262 – 267
10.	Practice Sheet-I	268 – 288
11.	Practice Sheet-II	289 – 304



SURVEYING PRINCIPLE'S

THEORY

Definition of Surveying

- ❖ Surveying is the science or art of making the measurements necessary to determine or establish the relative positions of points. The points may be on, above or below the surface of the earth. Surveying is done to ascertain and delineate on map or plan the shape and extent of any portion of the earth's surface:

Divisions of Surveying

- ❖ Primarily Surveying can be divided into two classes
 1. Plane Surveying and
 2. Geodetic surveying.
- ❖ **1. Plane Surveying :**
 - ❖ In plane surveying the curvature of the earth's surface is neglected. The earth's surface is considered plane. The line connecting any two points on the surface of the earth is considered straight line and the angles of polygons as plane angles. This type of survey is adopted when surveys extend over small area.
- ❖ **2. Geodetic Surveying :**
 - ❖ This method of survey is adopted when large distances and areas are to be covered. In it the curvature of the earth is considered in all the measurements taken on the surface of the earth. All the lines in the surface of the earth are curved lines and all the polygons formed on the surface are spherical polygons. This survey is also called trigonometrical survey.
 - ❖ The main characteristics of Geodetic survey
 - (1) very large distances and areas.
 - (2) use of very precise instruments
 - (3) use of refined method of observation
 - (4) high degree of precision.

Classification of Surveys

1. *Based upon the nature of field of survey :*

- (1) **Land survey :**
 - ❖ This survey work is done on the land only. It can be divided into following types.
 - (i) Topographical surveys.
 - (ii) City surveys.

- (iii) Cadastral surveys. they are also conducted for fixing the position of pathways, properties; transfer of land from one owner to another. boundaries of districts, States, Municipalities and even countries are fixed by this survey.
- (2) Astronomical Survey.
- (3) Marine or Navigation Surveys.

2. Based on the Object of Surveying

- (1) Engineering surveys.
- (2) Military surveys.
- (3) Geological surveys.
- (4) Archaeological surveys.

3. Based upon the Instruments used

- (1) Chain survey.
- (2) Compass survey.
- (4) Theodolite survey.
- (5) Tacheometric survey.
- (6) Photographic survey.
- (7) Aerial survey.
- (8) Levelling

4. Based upon the method employed in survey.

- (1) Triangulation survey.
- (2) Traverse survey.

PRINCIPLES OF SURVEYING :

1. **In order to fix the location of any point measurements from two reference points whose position are known have to be taken :**
 - ❖ According to this fundamental, for the location of the relative position, of any point at least two measurements are required from reference points the positions of reference points being already fixed. The two measurements from reference points may be (i) linear measurements (ii) angular measurements (iii) linear and angular measurements.
 2. **To work from whole to part**
 - ❖ According to this principle of surveying first of all a system of control points is fixed covering whole of area to be surveyed with very high degree of precision.
 - ❖ The object of this system of working is to prevent the accumulation of error and to control and localise the minor errors.
- (1) Engineer's scale :**
- ❖ In this method of representation of scale 1 cm on the plane represents some whole number of metres on the ground.

(2) Representative Fraction (R.F.) method :

- ❖ According to this method one unit length on the plane represents so many units of length on the ground. The ratio of plane distance to the corresponding ground distance is independent of units and is called representative fraction (R.F.) R.F. can be very easily found for any given Engineer's scale.

(3) Graphical scale :

- ❖ The scale may be represented on the plane graphically. It should be represented near the title of the map so that it is readily visible.

Types of Scales :

- ❖ The scales may be classified under following four heads.

- (1) Plain scale.
- (2) Diagonal scale.
- (3) Vernier scale.
- (4) Scale of chords.

PLAIN SCALE :

- ❖ A plain scale consists of a line divided into suitable number of equal parts or unit. The first part is subdivided into smaller part. Plain scales represent either two units or a unit and its sub-division such as metres and decimetres, miles and furlongs, units and tenths etc.

Diagonal Scale :

- ❖ Diagonal scale is used to read three dimensions such as metres, decimetres and centimetres, units, tenths and hundredths, yard, feet and inches, etc.
- ❖ The principle of construction of a diagonal scale is based upon the fact that similar triangles have their like sides proportional.

Comparative Scales

- ❖ Scales having same R.F. but graduated to read different units are called comparative scales. Comparative scales may be plain scales or diagonal scales.

Vernier Scale

- ❖ Vernier scales are used to read very small units with great accuracy. Vernier scale consists of two parts—a primary scale and a vernier. The primary scale is nothing but plain scale fully divided into minor divisions.

Types of Verniers

- ❖ Vernier may be divided into two classes

1. Direct and
2. Retrograde.

1. Direct vernier :

- ❖ In direct vernier the smallest division on the vernier is shorter than the smallest division on the main scale. In it n divisions of vernier are equal in length to $(n - 1)$ divisions of the primary or main scale.

s = value of smallest divisions of main scale.

v = value of smallest divisions on the vernier

n = number of divisions on vernier.

Since n divisions of vernier are equal to $n - 1$ divisions of the main scale

$$nv = (n - 1) s$$

$$v = \left(\frac{n-1}{n} \right) s = \left(1 - \frac{1}{n} \right) s$$

- ❖ Least count (L.C.) = $s - v = s - \left(\frac{n-1}{n} \right) s = \frac{s}{n}$. Thus L.C. division by total number of divisions on the vernier. Least count of the vernier is the difference between the smallest division on the main scale and smallest division on the vernier.

2. Retrograde vernier :

- ❖ In this case the length of smallest division on the vernier is longer than the smallest division on the main scale. If n divisions of the vernier are equal in length to $n + 1$ divisions of the main scale.

In this case also $nv = (n + 1) s$

$$v = \left(\frac{n+1}{n} \right) s$$

$$\text{L.C.} = v - s = \left(\frac{n+1}{n} \right) s - s = \frac{s}{n}$$

SHRUNK SCALE :

- ❖ If a graphical scale is not constructed on an old map and map has shrunk, it becomes necessary to find the shrunk scale of the map so that map could be correctly interpreted. R.F. of the original scale is known. The distance between two points on the map is measured and then compared with the corresponding distance on the map as calculated from the given scale or R.F. The ratio of the shrunk length to the true length is known as the shrinkage factor which is obviously less than unity. The shrunk scale is then obtained as follows.
- ❖ Shrunken scale = shrinkage factor \times original scale of the map.

- ❖ If R.F. of the original scale is $\frac{1}{1000}$ and shrinkage factor is $\frac{10}{11}$. The R.F. of shrunk scale shall be $\frac{10}{11} \times \frac{1}{1000} = \frac{1}{1100}$ i.e. 1 cm, = 11 m.

MEASUREMENT WITH WRONG SCALE :

- ❖ If any measurement on the map has been taken with a wrong scale the distance so measured will be wrong. The true distance and areas can be found by using following relations.

$$\text{True length} = \left(\frac{\text{Wrong scale}}{\text{Correct scale}} \right) \times \text{Measured length.}$$

$$= \left(\frac{\text{R.F. wrong scale}}{\text{R.F. of correct scale}} \right) \times \text{Measured length.}$$

$$\text{True area} = \left(\frac{\text{R.F. wrong scale}}{\text{R.F. of correct scale}} \right)^2 \times \text{Calculated area.}$$

SOME IMPORTANT DEFINITIONS :**1. Accuracy.**

- ❖ The degree of perfection obtained in observations, instruments use, and the methods employed, is known as the accuracy.
- ❖ Accuracy depends on the :
 - (1) precision of the instruments used
 - (2) precision of the methods used
 - (3) perfectness of the planning and
 - (4) perfectness of the observations.

2. Error :

- ❖ The difference between the true value and the measured value of any thing is known as the error.

3. Discrepancy :

- ❖ It is the difference between the two measured value of the same quantity. It is not an error. A discrepancy may be small, yet the error may be large. Discrepancy does not reveal the magnitude of systematic errors.

4. Precision :

- ❖ It denotes relative or apparent nearness to the truth and is based upon the refinement of the measurements and the size of the discrepancies.

SOURCES OF ERRORS :

1. Natural errors.
2. Instrumental errors.
3. Personal errors.

PROBABILITY :***Most probable value :***

- ❖ It is that value of a quantity which has more chances of being correct than any other quantity. The most probable error is that quantity which when added to and subtracted from the most probable value fixed the limits within which the true value of measured quantity must lie.

THEORY OF ERRORS :

- ❖ The probable error of a single measurement is obtained from the equation.

$$PE = \pm 0.6745 \sqrt{\frac{\sum d^2}{n-1}}$$

- ❖ The probable error of the mean of a number of observations of the same quantity is calculated from the equation.

$$PE_m = \pm 0.6745 \sqrt{\frac{\sum d^2}{n(n-1)}}$$

Principle of least squares :

- ❖ The principle of least squares which is developed from the law of probability, requires adjusting the observed values so as to produce a minimum sum of the squares of the errors (residuals)

Example: A Philadelphia rod has the main scale graduations in centimetres. Design a suitable retrograde vernier to read upto 1 mm.

Sol. Least Count = $\frac{s}{n}$,

$$\text{Here, } 1 = \frac{10}{n} \text{ or } n = 10$$

Ten divisions of the vernier should be equal to 11 divisions of the main scale.

Example: A surveyor measured the distance between two points marked on the plan drawn to a scale of 1 cm = 1m (R.F. = 1 : 100) and found it to be 50m. Later he detected that he used a wrong scale of 1 cm = 50 cm (R.F. = 1 : 50) for the measurement. Determine the correct length.

(b) What would be the correct area if the measured area is 60 m²?

Sol. Correct length = $\frac{\text{R.F. of the wrong scale}}{\text{R.F. of the correct scale}} \times \text{measured length}$

$$= \frac{1/50}{1/100} \times 50 = 100\text{m}$$

$$\text{correct area} = \left(\frac{1/50}{1/100} \right)^2 \times 60 = 240 \text{ m}^2$$

Example : Design a direct vernier for a theodolite circle having main scale graduations upto 20 minutes (20') if the least count required is 20 seconds (20").

Sol. Least Count = $\frac{s}{n}$,

$$\text{Here, } 20'' = \frac{20 \times 60}{n}, n = 60$$

As in the case of a direct vernier, n divisions of the vernier are equal to (n-1) divisions of the main scale, 60 divisions of the vernier scale should be equal to 59 divisions of the main scale. A length of 59 divisions of the main scale should be taken and divided into 60 divisions to form the vernier scale.



OBJECTIVE PRACTICE SHEET

SURVEYING PRINCIPLE'S

OBJECTIVE QUESTIONS

1. The required slope correction for a length of 60m, along a gradient of 1 in 20 is: [GATE-1990]
 - (a) 7.50 cm
 - (b) 0.750 cm
 - (c) 75.0 cm
 - (d) 5.50 cm

2. Systematic errors are those errors [GATE-1990]
 - (a) whose effects are cumulative and can be determined
 - (b) on circumference of circumscribing circle
 - (c) outside the great triangle
 - (d) in the centre of the circumscribing circle

3. The length of a base line measured on ground at an elevation of 300metres above mean sea level is 2250 meters. The required correction to reduce to sea level length, (given the radius of earth is 6370 km) is _____ [GATE-1991]

4. It is required to produce a small-scale map of an area in magnetic zone by directly plotting and checking the work in the field itself. Which one of the following surveys will be most appropriate for purpose? [IES-1995]
 - (a) Chain
 - (b) Theodolite
 - (c) Plane table
 - (d) Compass

5. The sensitiveness of a bubble tube in a level would decrease if [IES-2001]
 - (a) the radius of curvature of the internal surface of the tube is increased
 - (b) the diameter of the tube is increased
 - (c) the length of the vapour bubble is increased
 - (d) the viscosity of the liquid is increased

6. Which one of the following surveys is employed for collecting sufficient data in connection with sewage disposal and water supply works? [IES-2002]
 - (a) Topographic survey
 - (b) Cadastral survey
 - (c) Geodetic survey
 - (d) Cross-sectioning and profile levelling

7. Match List-I (Type of survey) with List-II (Purpose) and select the correct answer using the codes given below the lists: [IES-2004]

<i>List-I</i>	<i>List-II</i>
A. Topographical survey B. Reconnaissance survey C. Cadastral survey D. Archaeological survey	1. To determine boundaries of fields, houses, etc. 2. To find relics of antiquity 3. To determine natural features of a country 4. To determine possibility and rough cost of the surveying system to be adopted

- Codes: A B C D

(a) 3	4	1	2
(b) 3	1	4	2
(c) 2	4	1	3
(d) 2	1	4	3

8. The plan of a map was photo copied to a reduced size such that a line originally 100 mm, measures 90 mm. The original scale of the plan was 1 : 1000. The revised scale is [GATE-2007]
 - (a) 1 : 900
 - (b) 1 : 1111
 - (c) 1 : 1121
 - (d) 1 : 1221

9. The plan of a survey plotted to a scale of 10m to 1 cm is reduced in such a way that a line originally 10cm long now measures 9 cm. the area of the reduced plan is measured as 81 cm². The actual area (m²) of the survey is
[GATE-2008]
- (a) 10000 (b) 6561
(c) 1000 (d) 656
10. The survey in which the earth curvature is also considered is called
[GATE-2008]
- (a) Geodetic survey
(b) plane survey
(c) preliminary survey
(d) topographical survey
11. Which one of the following conditions requires geodetic surveying?
[IES-2009]
- (a) Horizontal curve ranging
(b) Vertical curve ranging
(c) Survey of a country
(d) Reconnaissance survey
12. The subtense tacheometry method is adopted when the ground is
[IES-2012]
- (a) Flat (b) Inclined
(c) Undulating (d) A waterbody
13. Which one of the following statements is correct?
[IES-2013]
- (a) In a retrograde vernier, (n - 1) divisions on the primary scale are divided into n divisions on the vernier scale
(b) A double vernier consists of two simple verniers placed end-to-end forming one scale with the zero in the centre
(c) In an extended vernier, (2n + 1) primary divisions are divided into n divisions on the vernier
(d) In a direct vernier, (n+1) primary divisions are divided into n equal divisions on the vernier scale.
14. The survey carried out to delineate natural features, such as hills, rivers, forests and man-made features, such as towns, villages, buildings, roads, transmission lines and canals is classified as
[GATE-2014]
- (a) engineering survey
(b) geological survey
(c) land survey
(d) topographic survey
15. *Assertion (A)* : Multistage imaging refers to viewing a given area in several narrow bands.
Reason (R) : Multistage imaging is also called spatial resolution.
[IES-2014]
- (a) both A and R are individually true and R is the correct explanation of A
(b) both A and R are individually true but R is not the correct explanation of A
(c) A is true but R is false
(d) A is false but R is true
16. Which of the following scales is the largest one
- (a) 1 cm = 50 m (b) 1 : 42 000
(c) RF = 1/300 000 (d) 1 cm = 50 km
17. The shrinkage factor of an old map is 24/25 and the RF of original map is 1/2400, then the corrected scale for the map is
- (a) 1/2400 (b) 1/2500
(c) 1/600 (d) 1/60000
18. The RF of scale 1 cm = 1 km is
- (a) 1/100000 (b) 1/10000
(c) 1/100 (d) 1/10
19. The smallest length that can be drawn on a map is
- (a) 0.25 mm (b) 0.5 mm
(c) 10 mm (d) 15 mm
20. The main plate of a transit is divided into 1080 equal divisions. 60 divisions of the vernier coincide exactly with 59 divisions of the main plate. The least count (in seconds) of the transit is
- (a) 5 (b) 10
(c) 15 (d) 20
21. The difference in the length of an arc and its subtended chord on earth's surface for a distance of 18.5 km is about
- (a) 0.1 cm (b) 1.52 cm
(c) 10 cm (d) 100 cm
22. Surveys which are carried out to provide a national grid of control for preparation of accurate maps of large areas are known as
- (a) Plane surveys
(b) Geodetic surveys
(c) Geographical surveys
(d) Topographical surveys

23. Surveys which are carried out to depict mountains, water bodies, woods and other details are known as
- Cadastral surveys
 - City surveys
 - Topographical surveys
 - Hydrographic surveys
24. The effect of the curvature of the earth's surface is taken into account only if the extent of surveys is more than
- 100 km²
 - 260 cm²
 - 195.5 km²
 - 300 km²
25. Match the following:
- Section-I**
- Topographical survey
 - Cadastral surveys
 - City survey
 - Engineering surveys
- Section-II**
- To determine the natural features of a country such as hills, valley, rivers, nuallas, lakes, woods, etc.
 - To survey for the features such as roads, railways, canals, buildings, towns, villages, etc.
 - To locate the boundaries of fields, houses, etc
 - To determine quantities and for collection of data for road, railways, reservoirs, sewerage, water supply scheme, etc.
 - For laying out plots and construction streets, water supply systems and sewers.
- I-A and B, II-C, III-E, IV-D
 - I-C, II-A and B, III-C, IV-E
 - I-D, II-A and B, III-C, IV-E
 - I-B, II-C, III-A, IV-D and E
26. Surveying is the art of determining the relative positions of points on, above or beneath the surface of the earth, with respect to each other, by the measurement of
- distance
 - directions
 - elevations
 - (i), (ii), (iii) are required
 - only (i) is required
 - only (ii) required
 - only (iii) is required
27. The main principle of surveying is to work from
- higher level to the lower level
 - lower level to the higher level
 - part to whole
 - whole to part
28. The error which occurs while conducting the survey from whole to part and part to whole is
- same
 - in whole to part, it is localized and in part to whole it is expanded
 - in whole to part it is expanded and in part to whole it is localized
 - in both the methods error is localized
29. A point R can be located by the two control points P and Q by
- measuring PR and QR from P and Q, measure distance of R and plot
 - dropping a perpendicular from R on PQ, meeting the line in S, measure PS, SQ and plot
 - distance QR and angle α between QR and QP
- only (i) is correct
 - by (i) and (ii) both
 - by (i), (ii) and (iii)
 - by none of them
30. The objective of a survey is to
- prepare a plan or map
 - determine the relative position of points
 - determine position of points in a horizontal plane
 - determine position of points in a vertical plane
- only (i) is correct
 - only (i) and (ii) are correct
 - (i), (ii), (iii), (iv) all are correct
 - none of them are correct